



Features

- Die-cast aluminium
- PCB protection shell
- Easy installation
- Fanless cooling
- Front access
- 2 Years Standard Warranty (extendable up to 3 years)

The Orion P1.56 Indoor Bellatrix Series combines innovative design and superior performance for exceptional display solutions. Its die-cast aluminum cabinet features seamless splicing for a sleek, modern look and total front access for easy maintenance and replacement. With convenient flight plugs and side locks, installation becomes quick and straightforward. The Bellatrix Series is highly versatile, making it ideal for a range of applications, including LED TV monitoring centers and large-scale events.

Technical Specification

Product Parameter	P1.56
LED Type	COB
Pixel Pitch(mm)	1.5625
Pixel Density (pixels/ m ²)	409,600
Cabinet Dimension(mm)	600 x 337.5
Cabinet Resolution(dot)(WXM)	384 x 216
Module Dimension(mm)	150 x 168.75
Module Resolution(dot)(WXM)	96 x 108
Module quantity(WXM)	4x2
Cabinet material	Die-casting Aluminum
Viewing Angle	H 170° , V 170°
Brightness	≥600 m ²
Color uniformity	≥80%
Contrast Ratio	10000:1
Color Temperature	5000-12000 Optional
Frame-changing Frequently	50/60
Drive Method	1/48

Connection Technology	Common Anode
Refresh rate	≥3840HZ
Max. Power Consumption (w/m ²)	420
Avg. Power Consumption (w/m ²)	150
Service Access	TOTAL FRONT ACCESS
IP Grade	IP31
Operating Temp/Humidity	0°C~50°C, 10~90%RH
Storage Temp/Humidity	0°C~60°C, 10~90%RH
Weight/Cabinet(KGS)	≤4.5KGS
System Controller	Novastar

Specifications and product information are subject to change without prior notice due to ongoing innovation and development. For the most up-to-date details, please visit www.orion-led.com.

ATENTI | ORIGINS

ATENTI ORIGINS PHOTOELECTRICITY CONSORT PVT.LTD.

Reg. Office: 504, 5th Floor ABW Elegance Tower, Jasola District Centre, Jasola, New Delhi - 110025

Branch Offices: Lucknow, Mumbai, Hyderabad

Factory : B-10, Sector-88, Noida - 201301

