



Features

- UHD picture quality
- Light Weight
- Ultra-Thin Display
- Soft Rubber Module
- 2 years standard warranty (extendable up to 3 years)

The Orion P1.53mm Flexible Series LED display is a highly adaptable and innovative solution designed for creative and unconventional visual setups. Its strong magnetic flexible modules allow for front-service installation, making it ideal for complex and special-shaped structures where maintenance accessibility is crucial. Built with high-quality silicone materials for both the PCB base and tray—along with copper pillar welding and precise screw placements—the series ensures superior screen flatness and optimal visual performance.

Technical Specification

Model No.	P1.53
LED Type	Black SMD1212
Pixel Pitch(mm)	1.53
Drive Method	1/43
Module Size(mm)	320X160mm
Module Resolution(pixel)	208x104
Pixel Density	427,185pixels/m ²
Viewing Angle	H 140", V 140*
Brightness	300-800cd/m ²
Refresh Rate(Hz)	≥3840
Frame Rate(Hz)	≥50-60
Voltage(V)	AC 110/220V
Avg. Power Consumption	200W/m ²
Max. Power Consumption	600W/m ²
Service Access	Total Front Access

IP Grade	IP31
Operating Temp/Humidity	0C~50° °C ,10~90%RH
Storage Temp/Humidity	C-60° °C ,10~90%RH
Lifetime(Normal Temp)	≥100.000H@50% brightness
Cabinet Frame Size(mm)	Customized Cabinet
Cabinet Type and Material	Sheet metal
Screen resolution	Customized
Cabinet Weight (Kg)	32 KG Per sqm

Specifications and product information are subject to change without prior notice due to ongoing innovation and development. For the most up-to-date details, please visit www.orion-led.com.

ATENTI | ORIGINS

ATENTI ORIGINS PHOTOELECTRICITY CONSORT PVT.LTD.

Reg. Office: 504, 5th Floor ABW Elegance Tower, Jasola District Centre, Jasola, New Delhi - 110025

Branch Offices: Lucknow, Mumbai, Hyderabad

Factory : B-10, Sector-88, Noida - 201301

✉ sales@orion-led.com

in ORION LED

f @OrionLedDisplay

ig @orion_led_

yt @OrionLED

